Macadams
Self Cooking Center

Mac SCC 6Pan

Mac SCC 20Pan

Mac SCC 10Pan

FEATURES & BENEFITS

- Self Cooking Control with 7 cooking methods
- Combi-steamer mode with 3 modes:
  Temperature range 30°C - 300°C
- Integrated hand shower with automatic retraction system
- Core temperature probe with 6 point measurement
- ClimaPlus Control - humidity measured, set and regulated with 1% accuracy
- HiDensity Control - patented distribution of the energy in the cooking cabinet
- USB Port
- 350 programs with up to 12 steps
- 3 Stage variable humidification
- 5 Air speed, programmable

MACADAMS
FOOD SERVICE SOLUTIONS

Technical Specs

	MAC SELF COOKING CENTER		
	6 Pan	**10 Pan**	**20 Pan**
Capacity	6 x 1/1 GN	10 x 1/1 GN	20 x 1/1 GN
Number of Meals per Day	30 - 80	80 - 150	150 - 300
Lengthwise Loading	1/1, 1/2, 2/3, 1/3, 2/8 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN	1/1, 1/2, 2/3, 1/3, 2/8 GN
Width	847 mm	847 mm	879 mm
Depth	771 mm	771mm	791 mm
Height	782 mm	1042 mm	1782 mm
Water: ***Inlet*** ***Outlet*** ***Pressure***	 R3/4" DN 50 150 - 600 kPa or 0.15 - 0.6 Mpa	 R3/4" DN 50 150 - 600 kPa or 0.15 - 0.6 Mpa	 R3/4" DN 50 150 - 600 kPa or 0.15 - 0.6 Mpa
Weight	112.5 Kg	132.5 Kg	267 Kg
Connected Load	11 kW	18.6 kW	37 kW
Fuse	3 x 16 A	3 x 32 A	3 x 63 A
Mains Connection	400 V	400 V	400 V
"Dry Heat" Output	10.3 kW	18 kW	36 kW
"Steam" Output	9 kW	18 kW	36 kW

"The right unit for every need..."

Contact Details

HEAD OFFICE, EXPORTS & CAPE TOWN BRANCH Tel : +27 (21) 907-1000 Fax : +27 (21) 907-1111

JOHANNESBURG BRANCH Tel : (011) 472-4100 Fax : 086 618 6462

DURBAN BRANCH Tel : (031) 569-6290 Fax : (031) 569-6296

EMAIL info@macadams.co.za **WEBSITE** www.macadams.co.za