

Macadams Hopper Topper

(Econo & HTPL Pump System)




- All stainless steel piston pump unit.
- Mobile all stainless steel construction stand
- Adjustable height to suit customer's mixing bowl.
- Unique tilting mechanism allows for easy changing of bowls
- Automatic start/stop hopper level control sensor, enclosed in a nema 4x control box.
- 2" diameter flexible outlet hose with "u" pipe on the end to hook onto the rim of the hopper.
- The hopper topper pl is power lift model with a extra 8" extended lift distance and deeper bowl depth capabilities




Technical Specs

| | ECONO | HTPL | |
|--------------------------------|---|--------------------------------------|--|
| | LCONO | 1111 L | |
| Power | Air/Electric 100 PSI @ 4CFM, 110V, 1 Amp, single phase or 220V 6.9 Bar @ 226.5 litres/minute | Air Compression 4-12 CFM @ 80 PSI | |
| Speed | Variable with air pressure regulator. | | |
| Volume (l/min) | 11 - 49 | Max 60-79 | |
| Cube Size | Up to 25 mm cube soft fruit or similar. | | |
| Dimensions (mm) | 762 (W) x 1474 (L) x 840 (H) | | |
| Max. Bowl Height | Rim 1110 mm from ground level. | Rim 1110mm from ground level | |
| Max. Reach - to bottom of bowl | 660 mm from the bowl rim. | | |
| Weight (kg) | 113 | | |



| Α | Tilt Height | 1290 mm |
|---|---|---------|
| В | Maximum Bowl rim clearance in up position | 1040 mm |
| С | Distance between Pump inlet and outlet (Maximum Bowl Depth) | 620 mm |
| D | Maximum pump to floor clearance | 420 mm |
| E | Inside Width | 636 mm |
| F | Bottom Frame Height | 153 mm |



Contact Details

HEAD OFFICE, EXPORTS & CAPE TOWN BRANCH Tel: +27 (21) 907-1000 Fax: +27 (21) 907-1111

JOHANNESBURG BRANCH Tel: (011) 472-4100 Fax: 086 618 6462

DURBAN BRANCH Tel: (031) 569-6290 Fax: (031) 569-6296

EMAIL info@macadams.co.za WEBSITE www.macadams.co.za