

Rondo RondoStar & Compass



RONDOSTAR 4000 SFS

RONDOSTAR 4000 SFI



RONDO COMPAS 3000

FEATURES & BENEFITS

- Sturdy construction in stainless steel.
- Minimum side trimmings.
- Colour touch panel with large symbols.
- Gentle reeling up.
- Easy cleaning & less dusting flour in the atmosphere.
- Reliable operation.





Technical Specs

	RONDOSTAR 4000 SFS 6607H.EO	RONDOSTAR 4000 SFI 6607H.E6	COMPAS 3000 SFA6127H.A1
Model	A-frame base	Rigid construction with table support	Mobile, Rigid Sub-structure with table supports
Rated Power	2,0 kVa/1.2 kW	2,0 kVa/1.2 kW	2,0 kVa/1.2 kW
Control Voltage	-	-	-
Supply Voltage	3 x 200 - 420 V, 50/60 Hz	3 x 200 - 420 V, 50/60 Hz	3 x 200 - 420 V, 50/60 Hz
Width of Conveyor Belts (mm)	640	640	640
Table Dimensions (mm)	3500 (L)	3500 (L)	3505 (L) X 650 (W)
Roller Length (mm)	660	660	660
Safety Guard Opening (mm)	90	90	90
Roller Gap (mm)	0,2 – 45	0,2 – 45	0,2 – 45
Roller Gap Reduction	Motorized: 100 programs, manual	Motorized: 100 programs, manual	-
Speed of Discharge Conveyor (cm/ sec)	85	85	50 - 96
Required Floor Space in:			
Working position (mm)	1255 x 3820	1255 x 3820	1260 x 3820
Resting position (mm)	1255 x 3500	1255 x 3500	1260 x 3505
Automatic Flour Duster	With	With	With
Automatic Dough Reeler	Option	Option	With

Contact Details

HEAD OFFICE, EXPORTS & CAPE TOWN BRANCH Tel : +27 (21) 907-1000 Fax : +27 (21) 907-1111

JOHANNESBURG BRANCH Tel : (011) 472-4100 Fax : 086 618 6462

DURBAN BRANCH Tel : (031) 569-6290 Fax : (031) 569-6296

EMAIL info@macadams.co.za

WEBSITE www.macadams.co.za