

iCombi Classic Combi Oven



FEATURES & BENEFITS

- **Easy to use** : Dial with push function, colour display, clear symbols on the user interface, so that you can work intuitively and without errors.
- **Simple programing** : Individual programing with up to 100 programs, with multi-step cooking processes of up to 12 steps. For endlessly reproducible results
- **ClimaPlus** : Top dehumidification performance and the ability to set humidity in 10% stages create a precise cooking cabinet climate. For fast results.
- **Fan wheels** : Together with the cooking cabinet shape, up to 3 fan wheels provide optimal distribution of the heat providing high energy input into the food. For uniform results and high productivity.
- **Cleaning and descaling** : Automatic clean, including overnight, phosphate-free cleaner tabs and reduced consumption of detergent - it could not get cleaner than that. The care system also prevents scale.
- **LED cooking cabinet lighting** : With the high light intensity and neutral light colour, the external cooking level can be identified quickly.
- Double-glazed door with heat-reflecting coating
- Integrated hand shower
- Fresh steam generator
- Also, LAN/WiFi (optional), integrated door drip tray, centrifugal grease trap



	6 Pan	10 Pan	20 Pan	40 Pan
Capacity	6 × 1/1 GN	10 × 1/1 GN	20 × 1/1 GN	20 × 2/1 GN
Number of meals per day	30–100	80–150	150–300	300–500
Lengthwise loading (GN)	1/1. 1/2. 2/3. 1/3. 2/8 GN	1/1. 1/2. 2/3. 1/3. 2/8 GN	1/1. 1/2. 2/3. 1/3. 2/8 GN	2/1. 1/1 GN
Width	850 mm	850 mm	877 mm	1082 mm
Depth (including door handle)	842 mm	842 mm	913 mm	1117 mm
Height	754 mm	1014 mm	1807 mm	1807 mm
Water inlet	R 3/4"	R 3/4"	R 3/4"	R 3/4"
Water outlet	DN 50	DN 50	DN 50	DN 50
Water pressure	1.0 - 6.0 bar	1.0 - 6.0 bar	1.0 - 6.0 bar	1.0 - 6.0 bar
ELECTRIC				
Weight	93 kg	121kg	231kg	304 kg
Connected load	10.8 kW	18.9 kW	37.2 kW	67.9 kW
Fuse	3 × 16 A	3 × 32 A	3 × 63 A	3 × 100 A
Mains connection	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V
Convection mode output	10.25 kW	18 kW	36 kW	66 kW
Steam mode output	9 kW	18 kW	36 kW	54 kW
GAS				
Weight	101 kg	139 kg	276 kg	371 kg
Electrical rating	0.6 kW	0.9 kW	1.3 kW	2.2 kW
Fuse	1 × 16 A	1 × 16 A	1 × 16 A	1 × 16 A
Mains connection	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V	1 NAC 230 V
Gas supply/connection	3/4" IG	3/4" IG	3/4" IG	3/4" IG

iCombi® Classic.

Productive. Robust. Reliable.



Contact Details

HEAD OFFICE, EXPORTS & CAPE TOWN BRANCH Tel : +27 (21) 907-1000 Fax : +27 (21) 907-1111

JOHANNESBURG BRANCH Tel : (011) 472-4100 Fax : 086 618 6462

DURBAN BRANCH Tel : (031) 569-6290 Fax : (031) 569-6296

EMAIL info@macadams.co.za

WEBSITE www.macadams.co.za