

Macadams

iCombi Pro Combi Oven

iCombi Pro XS



iCombi Pro 20Pan



iCombi Pro 10Pan



iCombi Pro 6Pan



FEATURES & BENEFITS

- **Efficient food production** : The iProduction Manager plans production processes and indicates which foods are best cooked together. Streamlines processes, saves time and energy.
- **Ultrafast cleaning** : A clean unit in approx. 12 minutes, this can only be done by the iCombi Pro. Even the standard clean saves 50%* in time and cleaner. Stay clean, less downtime, more productive time.
- **Carefully designed** : More fan wheels, optimised cooking cabinet shape, increased dehumidification performance all mean up to 50%* larger loads and even better food quality. For even higher productivity.
- **iDensityControl** : Higher performance, which saves time and money. Adding more to the flavour.
- LED lighting with rack signaling
- 6-point core probe
- Dynamic air circulation and Fresh steam generator
- 300 °C maximum cooking cabinet temperature
- Integrated hand shower with jet and spray function
- Triple-glazed cooking cabinet door
- Also, energy consumption display, new sealing technology for floor units, WiFi without external antenna



	XS Unit	6 Pan	10 Pan	20 Pan	40 Pan
Capacity	6 × 2/3 GN	6 × 1/1 GN	10 × 1/1 GN	20 × 1/1 GN	20 × 2/1 GN
Number of meals per day	20–80	30–100	80–150	150–300	300–500
Lengthwise loading (GN)	1/2. 2/3. 1/3. 2/8 GN	1/1. 1/2. 2/3. 1/3. 2/8 GN	1/1. 1/2. 2/3. 1/3. 2/8 GN	1/1. 1/2. 2/3. 1/3. 2/8 GN	2/1. 1/1 GN
Width	655 mm	850 mm	850 mm	877 mm	1082 mm
Depth (including door handle)	621 mm	842 mm	842 mm	913 mm	1117 mm
Height	567 mm	754 mm	1014 mm	1807 mm	1807 mm
Water inlet	R 3/4"	R 3/4"	R 3/4"	R 3/4"	R 3/4"
Water outlet	DN 40	DN 50	DN 50	DN 50	DN 50
Water pressure	1.0 - 6.0 bar	1.0 - 6.0 bar	1.0 - 6.0 bar	1.0 - 6.0 bar	1.0 - 6.0 bar
ELECTRIC					
Weight	67 kg	99 kg	127 kg	263 kg	336 kg
Connected load	5.7 kW	10.8 kW	18.9 kW	37.2 kW	67.9 kW
Fuse	3 × 10 A	3 × 16 A	3 × 32 A	3 × 63 A	3 × 100 A
Mains connection	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V	3 NAC 400 V
Convection mode output	5.4 kW	10.25 kW	18 kW	36 kW	66 kW
Steam mode output	5.4 kW	9 kW	18 kW	36 kW	54 kW
GAS					
Weight	117 kg		155 kg	284 kg	379 kg
Electrical rating	0.6 kW		0.9 kW	1.3 kW	2.2 kW
Fuse	1 × 16 A		1 × 16 A	1 × 16 A	1 × 16 A
Mains connection	1 NAC 230 V		1 NAC 230 V	1 NAC 230 V	1 NAC 230 V
Gas connection	3/4" IG		3/4" IG	3/4" IG	3/4" IG

iCombi® Pro.

The new standard.



Contact Details

HEAD OFFICE, EXPORTS & CAPE TOWN BRANCH Tel : +27 (21) 907-1000 Fax : +27 (21) 907-1111

JOHANNESBURG BRANCH Tel : (011) 472-4100 Fax : 086 618 6462

DURBAN BRANCH Tel : (031) 569-6290 Fax : (031) 569-6296

EMAIL info@macadams.co.za

WEBSITE www.macadams.co.za